

# DINGO<sup>®</sup>

**MODEL K9CT**

**WARRANTY 5 YRS / 5000 HRS**



[WWW.DINGO.COM.AU](http://WWW.DINGO.COM.AU)

# WHAT YOU GET

- The ORIGINAL DiNGO®
- Designed and manufactured in Australia
- Latest Low Emission range of Engines
- Best in class Traction and Trenching
- No Steel-on-Steel Wear
- Ultra Heavy Duty Powder coated Finish

# PERFORMANCE

Engine	27 HP Yanmar
Hydraulic pumps	3 pumps
Pump sizes	6, 8.4 & 8.4 cc
Relief pressure (AUX)	3,400 psi (235 bar)
Hydraulic output	73 L/m
Max travel speed	9.5 km / h
Rated lift capacity	440 kg

## Direct drive trax system

- 1 Through 2 specifically designed and OEM manufactured Hydraulic Drive Motors

## High Flow Auxiliary Hydraulics

- 2 For powering attachments through the toughest conditions.

## Grease free

- 3 For Lower Cost maintenance and Quick hitch system.

## 180° access

- 4 Safer for operators - no risk of being trapped from behind and side bars.

## Soft touch controls

- 5 Minimise fatigue while providing accurate control.

## 1,855mm lift

- 6 Lifts into utes & most trucks, tips over fences.

## Rupture resistant fuel tank

- 7 Full vented cap with true-fill opening for easier refuelling.

# DIMENSIONS

Overall width	1,020 mm
Overall length	1,600 mm
Overall height	1,225 mm
Max operating height 4 in 1	2,680 mm
Turning radius with 4 in 1 bucket	1,300 mm
Angle of departure	25°
Wheel base	800 mm
Ground clearance	155 mm
Dump height standard bucket	1,550 mm
Dump height 4 in 1 bucket	1,870 mm
Reach fully raised 4 in 1 bucket	800 mm
Height to hinge pin	1,985 mm
Machine width 4 in 1 bucket	1,050 mm & 1,200 mm
Hydraulic reservoir capacity	76 L
Machine mass	1,180 kg
Warranty	5 yrs / 5,000 hrs

*(In accordance with Dingo warranty Terms & Conditions)*



E&OE (Errors and omissions excepted).

[WWW.DINGO.COM.AU](http://WWW.DINGO.COM.AU)