DINGO®

MODEL K9CW WARRANTY 5 YRS / 5000 HRS



WWW.DINGO.COM.AU

WHAT YOU GET

- The ORIGINAL DiNGO®
- Designed and manufactured in Australia
- Latest Low Emission range of Engines
- Best in class Traction and Trenching
- No Steel-on-Steel Wear
- Ultra Heavy Duty Powder coated Finish
- Narrow wheel option for tight spaces

PERFORMANCE

Engine27 HP YanmarHydraulic pumps3 pumpsPump sizes6, 8.4 & 8.4 ccRelief pressure (AUX)3,400 psi (235 bar)Hydraulic output73 L/mMax travel speed9.5 km / hRated lift capacity440 kg

All wheel drive system

 Through 4 specifically designed and OEM manufactured Hydraulic Drive Motors

High Flow Auxiliary Hydraulics

2 For powering attachments through the toughest conditions.

Grease free

3 For Lower Cost maintenance and Quick hitch system.

180° access

4 Safer for operators - no risk of being trapped from behind and side bars.

Soft touch controls

5 Minimise fatigue while providing accurate control.

1,840mm lift

6 Lifts into utes & most trucks, tips over fences.

Rupture resistant fuel tank

7 Full vented cap with true-fill opening for easier refuelling.

E&OE (Errors and omissions excepted).

WWW.DINGO.COM.AU

DIMENSIONS

| Overall width | 780 mm & 1,040 mm |
|--|-------------------|
| Overall length | 1,600 mm |
| Overall height | 1,225 mm |
| Max operating height 4 in 1 | 2,690 mm |
| Turning radius with 4 in 1 bucket | 1,300 mm |
| Angle of departure | 25° |
| Wheel base | 800 mm |
| Ground clearance | 160 mm |
| Dump height standard bucket | 1,550 mm |
| Dump height 4 in 1 bucket | 1,870 mm |
| Reach fully raised 4 in 1 bucket | 800 mm |
| Height to hinge pin | 1,985 mm |
| Machine width 4 in 1 bucket | 1,050 mm |
| Hydraulic reservoir capacity | 76 L |
| Machine mass | 1,093 kg |
| Warranty | 5 yrs / 5,000 hrs |
| (In accordance with Dingo warranty Terms & Conditions) | |

(In accordance with Dingo warranty Terms & Conditions)



DINGO