DINGO®

MODEL K9PT

WARRANTY 5 YRS / 5000 HRS



WHAT YOU GET

- The ORIGINAL DINGO®
- Designed and manufactured in Australia
- Latest Low Emission range of Engines
- Best in class Traction and Trenching
- No Steel-on-Steel Wear
- Ultra Heavy Duty Powder coated Finish

PERFORMANCE

Engine 23 HP Kohler Hydraulic pumps 2 pumps

Pump sizes 11 & 4 cc

Relief pressure (AUX) 3,200 psi (220 bar)

Hydraulic output 47 L/m
Max travel speed 7.5 km / h
Rated lift capacity 325 kg

Direct drive trax system

1 Through 2 specifically designed and OEM manufactured Hydraulic Drive Motors

High Flow Auxiliary Hydraulics

2 For powering attachments through the toughest conditions.

Grease free

3 For Lower Cost maintenance and Quick hitch system.

180° access

4 Safer for operators - no risk of being trapped from behind and side bars.

Soft touch controls

5 Minimise fatigue while providing accurate control.

1,855mm lift

6 Lifts into utes & most trucks, tips over fences.

Rupture resistant fuel tank

7 Full vented cap with true-fill opening for easier refuelling.

E&OE (Errors and omissions excepted).

DIMENSIONS

Overall width 1,020 mm

Overall length 1,600 mm

Overall height 1,200 mm

Max operating height 4 in 1 2,680 mm

Turning radius with 4 in 1 bucket 1,300 mm

Angle of departure 25°

Wheel base 800 mm

Ground clearance 155 mm

Dump height standard bucket 1,450 mm

Dump height 4 in 1 bucket 1,835 mm

Reach fully raised 4 in 1 bucket 800 mm

Height to hinge pin 1,940 mm

Machine width 4 in 1 bucket 1,050 mm & 1,200 mm

Hydraulic reservoir capacity 76 L
Machine mass 989 kg

Warranty 5 yrs / 5,000 hrs

(In accordance with Dingo warranty Terms & Conditions)



