# DINGO®

## **MODEL K9PW**

WARRANTY 5 YRS / 5000 HRS



## **WHAT YOU GET**

- The ORIGINAL DINGO®
- Designed and manufactured in Australia
- Latest Low Emission range of Engines
- Best in class Traction and Trenching
- No Steel-on-Steel Wear
- Ultra Heavy Duty Powder coated Finish
- Narrow wheel option for tight spaces

## **PERFORMANCE**

23 HP Kohler Petrol **Engine** 

Hydraulic pumps 2 pumps 11 & 4 cc Pump sizes

Relief pressure (AUX) 3,200 psi (220 bar)

Hydraulic output 47 L/m 7.5 km / h Max travel speed Rated lift capacity 325 kg

#### All wheel drive system

Through 4 specifically designed and OEM manufactured Hydraulic Drive Motors

#### **High Flow Auxiliary Hydraulics**

**2** For powering attachments through the toughest conditions.

#### **Grease free**

3 For Lower Cost maintenance and Quick hitch system.

#### 180° access

4 Safer for operators - no risk of being trapped from behind and side bars.

#### Soft touch controls

5 Minimise fatigue while providing accurate control.

#### 1,840mm lift

6 Lifts into utes & most trucks, tips over fences.

#### Rupture resistant fuel tank

Full vented cap with true-fill opening for easier refuelling.

E&OE (Errors and omissions excepted).

## **DIMENSIONS**

Overall width

780 mm & 1.040 mm Overall length 1,600 mm Overall height 1,200 mm

Max operating height 4 in 1 2,680 mm Turning radius with 4 in 1 bucket 1,300 mm

25° Angle of departure

Wheel base 800 mm Ground clearance 140 mm 1,450 mm

Dump height standard bucket Dump height 4 in 1 bucket

Reach fully raised 4 in 1 bucket

Height to hinge pin

Machine width 4 in 1 bucket 1,050 mm & 1,200 mm

Hydraulic reservoir capacity 76 L Machine mass 862 kg

5 yrs / 5,000 hrs Warranty

1,835 mm

1,940 mm

800 mm

(In accordance with Dingo warranty Terms & Conditions)



